

# **GWT-10.1-1024600-AWMN-01**

## **Ver:10**

**TFT (Thin-Film-Transistor) Color Liquid Crystal Display Module**

<b>GW-</b>	<b>Global Wisdom Display</b>
<b>T</b>	<b>TFT Module</b>
<b>10.1</b>	<b>10.1" Diagonal</b>
<b>1024600</b>	<b>1024 RGB x 600 pixels</b>
<b>A-</b>	<b>Categories of models</b>
<b>W</b>	<b>Amorphous silicon TFT's IPS/ Glare</b>
<b>M-</b>	<b>Transmissive/Normal Black</b>
<b>N-</b>	<b>Without TP</b>
<b>01</b>	<b>Detail Number</b>
	<b>RoHS Compliant</b>

**Global Wisdom Display Co., Ltd**

[www.globalwisdomdisplay.com](http://www.globalwisdomdisplay.com) [www.gwdeshop.com](http://www.gwdeshop.com)

Business services: [GWDsales@globalwisdomdisplay.com](mailto:GWDsales@globalwisdomdisplay.com)

Technical service: [GWDtech@globalwisdomdisplay.com](mailto:GWDtech@globalwisdomdisplay.com)

*Never stop production, stock for sale, support small quantity, full of wide products range*

## Revision History

Revision	Date	Originator	Detail	Remarks
10	2016.09.09	Mary.liu	Initial Release	

## 1. Module General Parameter

Features	Details	Unit
Screen Size (Diagonal)	10.1"	
Panel type	IPS	
Display Mode	Transmissive /Normally Black	
Resolution	1024RGB x 600	
View Direction (human Eye)	FULL VIEW O'clock	Best Image
Module Outline	235 (H) x 143 (V) x 4.5(T)	mm
Active Area	222.72(H) x 125.28(V)	mm
Dot Size	0.2175 (H) x 0.2088 (V)	mm
Pixel Arrangement	-Strip	
Polarizer Surface Treatment	Anti-Glare	
Interface	24BIT RGB interface	
Driver IC	-	-
Display Colors	16.7M	
With or Without Touch Panel	Without	
Operating Temperature	-20~70	°C
Storage Temperature	-30~80	°C
Weight	TBD	g
Recommend connector	-	

## 2. Outline Drawing

